

MagWrite: USER GUIDE

Product	MagWrite - magnetic wallpaper, high receptivity
Description	<p>MagWrite has a high receptivity rating so works with both MagPlus and MagLite magnet types.</p> <p>MagWrite Matt has a non-reflective matt dry erase surface with features that include:</p> <ul style="list-style-type: none">- works as a projectable surface- easy to hang with multiple configurations- hard wearing matt PET surface for dry-erase or chalk pens - available in 120cm width and 3m, 6m 12m lengths <p>MagWrite Gloss has a highly reflective gloss dry erase surface with features that include:</p> <ul style="list-style-type: none">- smooth writeable surface, easy erase with microfibre pad or cloth- easy to hang with multiple configurations- hard wearing gloss PET surface for dry erase or chalk pens - available in 100cm x 5m and 120cm x 10m lengths
Receptivity Rating	4/5
Weight	1800 grammes per square metre
Fire Rating	EuroClass B when adhered to suitable substrate
Roll Dimensions	MagWrite Matt: 120cm width x 3m, 6m,12m lengths MagWrite Gloss: 100cm x 5m, 120cm x 10m lengths
Adhesives/Primers	MagFix Adhesive / PVA Primer, Tekfix VOV / Zinsser 'AllCoat' Solvent Base Primer
Warranty	7 Years
Maintenance:	<ul style="list-style-type: none">- MagWrite works with all high quality dry-erase pens (such as Artline Markers)- Clean with Whiteboard Spray and Microfibre Cloth (such as Cleaning Kit)- Regularly clean surface to keep in optimum condition- Important: Avoid felt pad cleaners and cheap pens as they can scratch the surface
Magnet Usage:	<ul style="list-style-type: none">- MagWrite has high receptivity so works with all magnet types- MagPlus are high power neodymium magnets for holding items- MagLite are low power sheet magnets for placement use
Health and Safety:	Warning - high power magnets can be dangerous if ingested and should not be used by children, always read safety information provided.
Classification:	This product is classified as non-hazardous and therefore does not require any special handling. This product does not require special labelling.
Fire Fighting:	Any extinguishing media are suitable. Wear self contained breathing apparatus, protective clothing and full face mask. Fumes should be ventilated immediately due to possible liberation of noxious gases.
Ecological:	This product is not bio-degradable. Dispose of in accordance with Local Authority regulations or via an authorised contractor.

IMPORTANT: MagScapes wallcoverings can act as a conductor of electricity due to the ferrous content in the vinyl - do not allow it to come into contact with exposed wires, and take care when installing around electrical wiring and boxes. Turn electricity off.



MagWrite: DECORATOR GUIDE

Configuration

It is recommended that MagWrite Wallcoverings are hung horizontally and positioned at optimum writing height for comfortable writing experience. Other configurations are possible as shown above.

Tools:

- A felt or sponge roller for paste application
- Scissors or sharp blade knife
- Straight edge
- Soft wallpaper brush
- Microfibre cloth or sponge

Wall preparation:

- MagWrite writing materials work best when applied to mirror smooth plaster surface
- ensure the wall surface is clean, dry, sound, mirror smooth and free from paint or chemicals
- best results will be obtained if the base plaster is sealed with a PVA sealer
- where necessary fill holes with filler and use fine sandpaper to smooth

Adhesives/Primers:

- **for plaster boards/walls:**
- prepare base wall with a PVA (Unibond Super PVA) to create a seal.
- apply a high-quality, ready-mixed adhesive (MagFix) or (Wallrock Power Adhesive) directly to the wall and apply pre-cut strips of wallcovering.
- **for mdf/plywood/panels:**
- prepare base panel with an oil based primer to create a seal (Zinsser 'AllCoat' Solvent Base Primer).
- apply a Tekfix VOV adhesive directly to the wall and apply pre-cut strips of wallcovering.

Hanging guide:

Note: We strongly advise that you test in advance before any major installation.

- for best writing experience it is recommended that MagWrite is applied horizontally
- allow wallcoverings to adjust to room temperature
- cut wallcovering into required lengths
- ensure wallcoverings are hung using the recommended adhesive/primer option (see above) - pour adhesive into a pasting tray and using a roller apply paste evenly to the wall (soaking is not necessary) cover an area to allow for 1-2 drops
- apply the cut lengths, edge to edge, vertically or horizontally as required
- apply MagWrite to the wall (black side to face the wall)
- use a soft clean wallpaper brush or microfibre cloth to flush out air bubbles and creases
- use masking tape to secure if likely to slip during install
- use a straight edge and sharp trimming knife at corners
- do not puncture air bubbles and do not use metal or sharp objects (other than the cutting knife) on the surface when installing the material
- remove any excess paste with a damp sponge and wipe surface clean- leave to dry thoroughly (min 24 hrs)

IMPORTANT: MagScapes wallcoverings can act as a conductor of electricity due to the ferrous content in the vinyl - do not allow it to come into contact with exposed wires, and take care when installing around electrical wiring and boxes. Turn electricity off.

Finishing options:

- Edging:**
- to prevent pens from skipping on to non writeable areas it is recommended that an edging strip is used
- Removal:**
- gently strip away from wall using a scraper
 - MagWrite will retain its receptive quality so may be re-used if undamaged on removal

IMPORTANT: MagScapes wallcoverings can act as a conductor of electricity due to the ferrous content in the vinyl - do not allow it to come into contact with exposed wires, and take care when installing around electrical wiring and boxes. Turn electricity off.