BoardsDirect

# APPLYING MAGNETIC PAINT

Here is how to apply our **Magnetic Paint** correctly, please follow these instructions

## 1 MEASURE YOUR AREA

- Ensure you have enough paint, measure the area.

## 2 PREPARE THE SURFACE

- Fill any holes or cracks in the surface with decorator's filler. Once the filler is dry, sand the surface to ensure it is smooth and remove any dust.

## 3 APPLYING MAGNETIC PAINT

- We recommend 3 coats of our Magnetic Paint. You can apply extra coats to increase the magnetic performance.
- Stir the magnetic paint before use.
- Prime any bare surfaces with a suitable primer.
- Apply a generous even coat of Smart Magnetic Paint to the surface leaving a smooth finish.
- Once the first coat is dry (after approx. 2 hours), lightly sand the surface and remove any sanding dust.
- Apply a generous even second coat of our Magnetic Paint. Allow to dry and sand lightly.
- Repeat the process until you have applied your desired number of coats.

## 4 MAGNETS

- Use neodymium magnets with your surface. Note: Ordinary household magnets are not suitable.

## 5 IDEAS

- Apply Boards Direct Whiteboard Paint on top to create a magnetic whiteboard surface.

### Colours

Pick a colour of your choice and apply on the top of your magnetic surface and you have a magnetic surface in any colour.